

EUROPEAN TRANSOM (2014)

| MODEL | 49E | | 53E | | 58E | | 62E | | 66E | | 70E | |
|--|-------------------------------|-----------|-------------------------------|-----------|---------------------------|-----------|-----------------------------|-----------|-----------------------------|-----------|-----------------------------|-----------|
| DIMENSIONS | FEET | METERS | FEET | METERS | FEET | METERS | FEET | METERS | FEET | METERS | FEET | METERS |
| Centerline Length | 53'2" | 16.21 | 56'7" | 17.25 | 59'1" | 18.01 | 63'11" | 19.48 | 69'5" | 21.16 | 71'3" | 21.72 |
| Length Overall LOA | 57'6" | 17.53 | 61'0" | 18.59 | 67'8" | 20.62 | 72'2" | 22.00 | 76'9" | 23.39 | 77'9" | 23.70 |
| Length Waterline LWL | 49'0" | 14.94 | 53'0" | 16.15 | 54'4" | 16.56 | 58'7" | 17.86 | 64'5" | 19.63 | 66'0" | 20.12 |
| Beam | 17'3" | 5.26 | 17'3" | 5.26 | 18'6" | 5.64 | 19'6" | 5.94 | 19'6" | 5.94 | 18'6" | 5.64 |
| Draft | 4'6" | 1.37 | 4'5" | 1.35 | 4'10" | 1.47 | 4'10" | 1.47 | 4'10" | 1.47 | 4'10" | 1.47 |
| Height Above Waterline to Radar Arch Top | 17'5" | 5.31 | 17'5" | 5.31 | 18'2" | 5.54 | 18'2" | 5.54 | 18'2" | 5.54 | 18'2" | 5.54 |
| WEIGHT | POUNDS | KILOGRAMS | POUNDS | KILOGRAMS | POUNDS | KILOGRAMS | POUNDS | KILOGRAMS | POUNDS | KILOGRAMS | POUNDS | KILOGRAMS |
| Displacement (approx.) | 61600 | 27941 | 66000 | 29937 | 69000 | 31300 | 78000 | 35400 | 84000 | 38102 | 81000 | 36740 |
| LIQUID CAPACITY | GALLONS | LITERS | GALLONS | LITERS | GALLONS | LITERS | GALLONS | LITERS | GALLONS | LITERS | GALLONS | LITERS |
| Fuel Capacity* | 1000 | 3785 | 1200 | 4542 | 1500 | 5678 | 2260 | 8555 | 3000 | 11356 | 2000 | 7571 |
| Water Capacity* — Domestic | 250 | 946 | 300 | 1136 | 300 | 1135 | 480 | 1817 | 500 | 1892 | 500 | 1893 |
| Holding Tank Capacity* — Black | 100 | 379 | 110 | 416 | 125 | 473 | 170 | 644 | 150 | 568 | 150 | 568 |
| Holding Tank Capacity* — Gray | 100 | 379 | 110 | 416 | 100 | 379 | 100 | 379 | 125 | 473 | 150 | 568 |
| POWER | | | | | | | | | | | | |
| Standard Power — Cummins® or Caterpillar® Diesel | Cummins® (2) 6.7 QSB 480HP | | Cummins® (2) 6.7 QSB 480HP | | Cummins® (2) QSB 550HP | | Cummins® (2) QSM11 715HP | | Cummins® (2) QSM11 715HP | | Cummins® (2) QSM11 715HP | |
| Standard Generator — Onan® or Kohler® Generators | Onan® (1) 13.5kW @ 60Hz | | Onan® (1) 13.5kW @ 60Hz | | Onan® (1) 17kW @ 60Hz | | Onan® (1) 21.5kW @ 60Hz | | Onan® (1) 21.5kW @ 60Hz | | Onan® (1) 21.5kW @ 60Hz | |

*Note - Fuel and water capacities may be affected by layout or mechanical changes.

In a continuing quest to improve its products Marlow Yachts Limited, Inc., and/or its subsidiaries and affiliates, reserve the rights to alter specifications and standards without notice to any party without obligation.



EUROPEAN TRANSOM (2014) CONT.

| MODEL | 74E | | 80E | | 88E | | 97E | |
|--|-----------------------------|-----------|-----------------------------|-----------|-----------------------------|-----------|---------------------------------|-----------|
| DIMENSIONS | FEET | METERS | FEET | METERS | FEET | METERS | FEET | METERS |
| Centerline Length | 78'3" | 23.85 | 84'0" | 25.60 | 91'11" | 28.01 | 97'7" | 29.74 |
| Length Overall LOA | 81'2" | 24.74 | 86'8" | 26.42 | 93'11" | 28.63 | 100'11" | 30.76 |
| Length Waterline LWL | 68'11" | 21.01 | 74'10" | 22.86 | 82'10" | 25.25 | 83'0" | 25.30 |
| Beam | 20'6" | 6.25 | 21'6" | 6.55 | 21'6" | 6.55 | 21'6" | 6.55 |
| Draft | 4'11" | 1.50 | 5'3" | 1.60 | 5'4" | 1.63 | 5'4" | 1.63 |
| Height Above Waterline to Radar Arch Top | 18'2" | 5.54 | 19'3" | 5.87 | 19'3" | 5.87 | 19'3" | 5.87 |
| WEIGHT | POUNDS | KILOGRAMS | POUNDS | KILOGRAMS | POUNDS | KILOGRAMS | POUNDS | KILOGRAMS |
| Displacement (approx.) | 92193 | 41818 | 125000 | 56699 | 140000 | 63503 | 158000 | 71668 |
| LIQUID CAPACITY | GALLONS | LITERS | GALLONS | LITERS | GALLONS | LITERS | GALLONS | LITERS |
| Fuel Capacity* | 3450 | 13060 | 3900 | 14763 | 4500 | 17034 | 5000 | 18927 |
| Water Capacity* — Domestic | 500 | 1893 | 600 | 2271 | 600 | 2271 | 600 | 2271 |
| Holding Tank Capacity* — Black | 200 | 757 | 235 | 889 | 200 | 757 | 200 | 757 |
| Holding Tank Capacity* — Gray | 200 | 757 | 235 | 889 | 200 | 757 | 200 | 757 |
| POWER | | | | | | | | |
| Standard Power — Cummins® or Caterpillar® Diesel | Cummins® (2) QSM11 715HP | | Cummins® (2) QSM11 715HP | | Cummins® (2) QSM11 715HP | | Caterpillar® (2) C-18 1015HP | |
| Standard Generator — Onan® or Kohler® Generators | Onan® (2) 27.5kW @ 60Hz | | Kohler® (2) 32kW @ 60Hz | | Kohler® (2) 32kW @ 60Hz | | Kohler® (2) 32kW @ 60Hz | |

*Note - Fuel and water capacities may be affected by layout or mechanical changes.

In a continuing quest to improve its products Marlow Yachts Limited, Inc., and/or its subsidiaries and affiliates, reserve the rights to alter specifications and standards without notice to any party without obligation.

