

EUROPEAN TRANSOM (2022)

MODEL	53E		58E		62E		66E		70E		75E	
DIMENSIONS	FEET	METERS	FEET	METERS	FEET	METERS	FEET	METERS	FEET	METERS	FEET	METERS
Centerline Length	61'7"	18.77	66'10"	20.37	68'5"	20.85	72'8"	22.15	77'7"	23.65	81'11"	24.97
Length Overall LOA	64'11"	19.79	70'6"	21.49	72'1"	21.97	76'4"	23.27	81'3"	24.77	85'7"	26.09
Length Waterline LWL	55'4"	16.87	59'10"	18.24	61'9"	18.82	65'10"	20.07	70'0"	21.34	74'0"	22.56
Beam	17'3"	5.26	18'6"	5.64	19'6"	5.94	19'6"	5.94	19'8"	5.99	20'6"	6.25
Draft	4'6"	1.35	4'10"	1.47	4'10"	1.47	4'10"	1.47	5'0"	1.52	5'0"	1.52
Height Above Waterline to Radar Arch Top	17'5"	5.31	18'2"	5.54	18'2"	5.54	18'2"	5.54	18'8"	5.69	18'2"	5.54
WEIGHT	POUNDS	KILOGRAMS	POUNDS	KILOGRAMS	POUNDS	KILOGRAMS	POUNDS	KILOGRAMS	POUNDS	KILOGRAMS	POUNDS	KILOGRAMS
Displacement (approx.)	70800	32114	79000	35834	91200	41368	100600	45631	110000	49895	118000	53524
LIQUID CAPACITY	GALLONS	LITERS	GALLONS	LITERS	GALLONS	LITERS	GALLONS	LITERS	GALLONS	LITERS	GALLONS	LITERS
Fuel Capacity*	1200	4542	1500	5678	2000	7571	2400	9085	3000	11356	3420	12946
Water Capacity* — Domestic	230	871	320	1211	370	1401	400	1514	400	1514	400	1514
Holding Tank Capacity* — Black	100	379	120	454	150	568	150	568	200	757	200	757
Holding Tank Capacity* — Gray	100	379	110	416	150	568	150	568	200	757	200	757
POWER												
Standard Power — Volvo® or John Deere® Diesel	Volvo® (2) 7.7L D8 550hp		Volvo® (2) 10.8L D11 670hp		John Deere® (2) 13.5L 750hp		John Deere® (2) 13.5L 750hp		John Deere® (2) 13.5L 750hp		Volvo® (2) 12.8L 800hp	
Standard Generator — Onan® or Kohler® Generators	Kohler® (1) 16kW @ 60Hz		Kohler® (1) 16kW @ 60Hz		Kohler® (1) 21kW @ 60Hz		Kohler® (1) 21kW @ 60Hz		Kohler® (1) 24kW @ 60Hz		Kohler® (2) 24kW @ 60Hz	

*Note - Fuel and water capacities may be affected by layout or mechanical changes.

In a continuing quest to improve its products Marlow Yachts Limited, Inc., and/or its subsidiaries and affiliates, reserve the rights to alter specifications and standards without notice to any party without obligation.



EUROPEAN TRANSOM (2022) CONT.

MODEL	80E		88E	
	FEET	METERS	FEET	METERS
Centerline Length	86'2"	26.26	94'6"	28.80
Length Overall LOA	89'10"	27.38	98'3"	29.95
Length Waterline LWL	79'5"	24.21	87'2"	26.57
Beam	21'7"	6.58	21'7"	6.58
Draft	5'3"	1.60	5'4"	1.63
Height Above Waterline to Radar Arch Top	19'3"	5.87	20'7"	6.27
WEIGHT	POUNDS	KILOGRAMS	POUNDS	KILOGRAMS
Displacement (approx.)	125000	56699	140000	63503
LIQUID CAPACITY	GALLONS	LITERS	GALLONS	LITERS
Fuel Capacity*	4000	15142	4000	15142
Water Capacity — Domestic*	500	1893	500	1893
Holding Tank Capacity* — Black	210	795	210	795
Holding Tank Capacity* — Gray	210	795	210	795
POWER				
Standard Power — Volvo® or John Deere® Diesel	Volvo® (2) 12.8L D13 900hp		Volvo® (2) 12.8L D13 900hp	
Standard Generator — Onan® or Kohler® Generators	Kohler® (2) 32kW @ 60Hz		Kohler® (2) 32kW @ 60Hz	

*Note - Fuel and water capacities may be affected by layout or mechanical changes.

In a continuing quest to improve its products Marlow Yachts Limited, Inc., and/or its subsidiaries and affiliates, reserve the rights to alter specifications and standards without notice to any party without obligation.

